

## DOMOBAR JUNIOR HX

Specifications	
<b>Manufacturer:</b>	VIBIEMME
<b>Model:</b>	Domobar Junior HX
<b>Machine Type:</b>	Semi-Auto
<b>Boiler Type:</b>	Heat Exchanger
<b>PID:</b>	No
<b>Basket Size:</b>	58 mm
<b>Coffee Boiler:</b>	1 L
<b>Steam Boiler:</b>	N/A
<b>Water Reservoir:</b>	2.0 L
<b>Electrical:</b>	240 volts / 1700 Watts / 7 Amp
<b>Dimensions:</b>	9" W x 17" D x 16" H
<b>Weight:</b>	28.1 Kg



Known for its history, style, and incredible build quality, Vibiemme has become a coveted machine since its introduction to the U.S. The Italian company based out of Milano, was started by three executives from the legendary Faema company. These men brought along their expertise and patent for the famous E61 grouphead. This commercial size grouphead (named after the year of its invention) is best known for its heavy brass composition for superior temperature stability as well as its passive pre-infusion system. The Vibiemme Junior model is an affordable and space saving alternative to the Vibiemme Super models.

### HIGHLIGHTED FEATURES

- Vibiemme's exclusive and original E-61 grouphead provides an active flow of water from the grouphead to the heat exchanger in the boiler as well as pre-infusion.
- The Heat Exchanger allows you to brew and steam milk simultaneously.
- Boiler and pump pressure gauges.
- Removable 2.0 liter pour-over water reservoir.
- Multi-directional steam and hot water wands.
- Large adjustable overpressure valve (OPV) which opens when there is too much pump pressure.

### STANDARD FEATURES

- Boiler capacity: 1 liter, 100mm diameter, solid, vertical copper boiler.
- Jaeger pressurstat monitors boiler pressure (which directly correlates to the temperature)
- 41 watt vibratory pump ("vibe" pump) rated up to 15 bar with air valve bypass
- Heavy vacuum breaker valve
- One-way valve to eliminate back pressure from the boiler
- Low water level light in middle indicates when water level in water reservoir in rear is low
- Large stainless steel drip tray which can be easily (slides out with pull of handle) removed for cleaning. Grate stays on machine when pulling out drip tray so that it is one step to empty